

288-core optical cable with 24-strand spectrum



Overview

Universal (Indoor/Outdoor) dry core optical fiber Multi Loose Tube cable with glass yarns as strength member and Low Smoke Zero Halogen outer jacket. Product feature: This cable has rodent protection by glass yarns. Existing out of 12 tubes with a diameter of 2.5mm with 288. 288 singlemode fibres for high density data center distribution applications. Each ribbon shall have its own sub-unit tube for easy handling and management. A1, Feet jacket marking, Yellow jacket color, B2ca flame rating. Corning® MiniXtend® HD Cables with Binderless* FastAccess® Technology are high-density micro cables that are up to 60 percent smaller and up to 70 percent lighter than standard loose tube cables and up to 20 percent smaller than standard micro cables. Providing high-fiber-counts in a rugged, compact design, the enhanced coupling features ensure the ribbon stack and cable act. Universal OFC MLT: GLASS YARNS + CST + LSZH with 12 Tubes of Ø2.



Article Content

Belden FISR288P5, OS2 288 STRAND Plenum Distribution Ribbon

Belden FISR288P5 is an indoor Plenum OS2 flexible ribbon fiber cable designed for high-density backbone and data center

810009727/DB | B-288-LN-8F-M24NS/17T 200 | CommScope

Fiber OSP cable, Zero Water Peak, ® Blown Micro Single Jacket All-Dielectric Outdoor Stranded Loose Tube 200um Fiber Arid-Core

Multi-Loose Tube Fiber Cable

Outdoor dry core optical fiber Multi Loose Tube cable with aramid yarns as strength member and polyethylene outer jacket. Existing

288 Fibre MicroCore® Stranded Loose Tube Cable

288 Fibre MicroCore® Stranded Loose Tube Cable MicroCore® Stranded cable comprising 288 optical fibres contained in jelly-filled

Outside Plant Fiber Optic Cable

Outside Plant Fiber optic cables for outdoor applications are engineered to withstand the more demanding conditions seen outside,

SOLO All-Dielectric Self-Supporting Cables 2-288 Fibers

SOLO® ADSS Cable, 72-Fibers Corning SOLO® cables are all-dielectric, self-supporting (ADSS) cables designed for

Fiber Identification Charts - 288-864 Fiber

Wrapping Tube Cable (WTC) with SpiderWeb Ribbon® (SWR®) This document provides direction on properly identifying the ribbon

UltraRibbon Indoor, Gel-Free Cables, 288

UltraRibbon Riser Gel-Free Cables, 288 Fibers | Photo PIM2570 Corning UltraRibbon™ Riser Gel-Free Cables continue the

288 Core Optical Fiber Cable

Discover 288 core optical fiber cables with high-density core count for FTTH and telecom networks. Ideal for long

288 Fibre MicroCore® Stranded Loose Tube Cable

288 Fibre MicroCore® Stranded Loose Tube Cable elly-filled loose tubes (24 fibres per tube). The tubes are laid up around a central

760240837 | N-288-MP-8Z-F24YL/30T

Fiber indoor cable, Low Smoke Zero Halogen Riser MPO Trunk, 288 fiber multi-unit with 24 fiber subunits, Singlemode G.652.D and

Product Spec Sheet 288ZV4-14100D53

Providing high-fiber-counts in a rugged, compact design, the enhanced coupling features ensure the ribbon stack and

288ZV5-14700S53 | RocketRibbon® Cable-250 288 F, Armored,

288ZV5-14700S53 RocketRibbon® Cable-250 288 F, Armored, Bend-Improved Single-Mode (OS2) Typically ships in 28 day (s)

GCCF288 Technical Data Sheet

Product feature: This cable has improved rodent protection by Corrugated Steel Tape (Full Rodent Protected). Existing out of 12

288 Fiber ADSS Cable, 288 Strand ADSS Fiber, 288 Fiber ADSS

We can deliver many ADSS cables from 2-288 Strands in 6-8 weeks or less-We now carry Fujikura ADSS cable direct

ALTOS® Loose Tube, Gel-Free Cable 288 F, Single-mode (OS2)

Gel-Free Loose Tube Optical Fiber Cables for Outdoor Applications ALTOS Generic Specifications Gel-free waterblocking

288ZH4-Y4F40A20 | MiniXtend® HD Cable with

MiniXtend HD cables have an SZ-stranded loose tube construction and provide high fiber counts in limited

Opti-Core 144 and 288-Fibre Indoor Ribbon Cables, LSZH and

This cable shall contain 144 or 288 singlemode fibres for high density data center distribution applications. The fibres shall be

288 strand fiber optic cable

Ribbon fiber cable is making a series of separate fiber (4F, 6F, 8F,12F and so on) bond each other, which is grouped together to be a

Product Spec Sheet 288ZVF-14101D20

288ZVF-14101D20 Corning FREEDM UltraRibbon riser cables provide the ultimate solution for indoor/outdoor high

288EV4-14100D53 | SST-UltraRibbon Single-Tube, Gel-Free Cable 288

Corning SST-UltraRibbon gel-free cables continue the innovative breakthrough in outdoor cable technology by introducing a new

Opti-Core 144 and 288-Fibre Indoor Ribbon Cables, LSZH and

288 singlemode fibres for high density data center distribution applications. The fibres shall be ribbonized for easy mass fusion

Product Spec Sheet 288EV4-14100D53

288EV4-14100D53 Corning SST-UltraRibbon gel-free cables continue the innovative breakthrough in outdoor cable technology by

GCRF288

Universal (Indoor/Outdoor) dry core optical fiber Multi Loose Tube cable with glass yarns as strength member and Low Smoke Zero

Product Spec Sheet 288EU5-T4101D20

288EU5-T4101D20 ALTOS® gel-free, double-jacket, single-armored cables are rugged, armored cables designed for direct-buried

Product Spec Sheet 288FUC-T4101D20

Explore Corning's optical communication solutions with detailed product specifications and features in this

288 Strand Fiber Optic Cable with OWIRE Solutions

The applications of a 288 strand fiber optic cable are vast and growing. In telecommunications, it forms the core of

SMF-28 Ultra Optical Fibers | SMF-28 Ultra 200 and

SMF-28 Ultra fiber is available in a traditional 242 µm diameter as well as a reduced 200 µm diameter

DX006DWLS9KR Indoor-Outdoor Fiber Optic Cable MM 288F

Simply put, applications requiring single mode and multimode fiber optic installations and areas such as data centers, office buildings

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://benniedesignstudio.co.za>

Email: sales@benniedesignstudio.co.za

Phone: +27 82 391 4765

Address: The Towers, 1 St Georges Mall, Cape Town, 8001, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

