

850nm polarization-maintaining optical fiber for field operations



Overview

The F-PM850 Polarization Maintaining Fiber offers low attenuation and excellent birefringence for high performance applications. This Corning PANDA PM fiber has a 850 nm operating wavelength with beat lengths ranging from less than 1. Requests for custom fiber pigtailed, different wavelengths and handling power of operation. These polarization-maintaining fiber optic patch cables are terminated on both ends with high-quality, narrow key, ceramic FC/PC connectors, featuring high-quality polish with a typical return loss of 50 dB. Each cable is individually tested to ensure the specified extinction ratio and insertion. The 780/830/850nm C-Lens Polarization Maintaining (PM) Fiber Collimator features a high-precision C-Lens design, ensuring efficient beam coupling and collimation for near-infrared wavelengths of 780nm, 830nm, and 850nm. 2x2 couplers are bidirectional and can be used to both split and combine signals (see the 2x2 Coupling Examples tab).



Article Content

F-PM850 Polarization Maintaining Optical Fiber

The F-PM850 Polarization Maintaining Fiber offers low attenuation and excellent birefringence for high performance applications.

Polarization-Maintaining Fiber Optical Patch Cable

These polarization-maintaining fiber optic patch cables are terminated on both ends with high-quality, narrow key, ceramic FC/PC

850 nm 2x2 Polarization-Maintaining Fiber Optic Couplers / Taps

These 2x2 Polarization-Maintaining (PM) Fiber Couplers are designed for operation at 850 nm and are available with a 50:50, 75:25,

850nm Polarization Maintaining PM Fiber Patch Cable, Slow Axis

With its combination of precision polarization control and flexible customization, this 850nm PM fiber patch cable is a reliable solution

PM Isolator

Polarization Maintaining Fiber Optical Isolator (850nm PM Isolator) is a fiber optic component that allows light to travel through a fiber

850nm polarization-maintaining optical fiber for field operations

PANDA PM Specialty Optical Fiber design uses two stress applying parts to create an extremely high birefringence,

F-PM850 Datasheet

The F-PM850 Polarization Maintaining Fiber offers low attenuation and excellent birefringence for high performance applications.

850nm Polarization Maintaining Optical Isolator

MECHANICAL DIMENSIONS return loss will be 5dB lower, and extinction loss will be 2dB lower. 2. The ER is for fiber ≤ 0.75

Polarization Maintaining Components 850nm Key Features

Description: Broadband TGG Based 850nm PM Optical Isolator, fast axis blocked, 1W power handling, continuous wave, PM780-HP

780/830/850nm Polarization Maintaining Fiber Collimator

The 780/830/850nm C-Lens Polarization Maintaining (PM) Fiber Collimator features a high-precision C-Lens design, ensuring

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://benniedesignstudio.co.za>

Email: sales@benniedesignstudio.co.za

Phone: +27 82 391 4765

Address: The Towers, 1 St Georges Mall, Cape Town, 8001, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

