

J185 Fiber Optic Connector



Overview

PRFIA-185-J-J-S – Adapter Coaxial Connector 1. Pricing and Availability on millions of electronic components from Digi-Key Electronics. A fiber optic connector is a mechanical device used to align and join optical fibers, enabling light to pass through with minimal loss. 85 mm (Jack) Straight Connector with a frequency range from DC to 67 GHz. It has a dielectric withstanding voltage (DWV) of more than 500 V (RMS) and a VSWR of less than 1. This PCB solderless edge launch connector has a stainless-steel body and. Here's the quality shows, conferences, and exhibitions for Samtec in August, 2026: OCP APAC August 11-12 | Taiwan | Website The Open Compute Project (OCP) is bringing together APAC communities for a very special two-day, in-person Summit to explore.

Article Content

Fiber Optic Connectors | TE Connectivity

TE's fiber optic connectors accommodate 10G Ethernet — with the capacity to handle next-generation 40G and 100G when needed

MMC Connectors

US Conec's MMC connector is a Very Small Form Factor (VSFF) multi-fiber optical connector designed for termination of single

Fiber Connector Types: A Complete Guide (2024)

It is a precise coupling device that joins fiber optic cables quickly, enabling faster connection and disconnection than

185-J-P-EP-ST-CM-1

The 185-J-P-EP-ST-CM-1 from Samtec is a 1.85 mm (Jack) Compression Mount Connector that operates from DC to 67 GHz. It has

185-J-P-EP-ST-EL-01

What is VNX+, the New Standard for Small Embedded Designs? VNX+ is a rugged, small-form-factor modular embedded computing

185-J-P-EP-ST-EL-01

The 185-J-P-EP-ST-EL-01 from Samtec is a 1.85 mm (Jack) Straight Connector with a frequency range from DC to 67 GHz. It has a

Fiber Connector Types: A Comprehensive Guide 2025

Among these components, fiber connector types are essential to network performance, reliability, and scalability. This

RFAA185J185J Bulgin | Coaxial Connector (RF) Adapters | DigiKey

RFAA185J185J - Adapter Coaxial Connector 1.85mm Jack, Female Socket To 1.85mm Jack, Female Socket 50 Ohms from Bulgin.

PRFIA-185-J-J-S Samtec Inc. | Connectors, Interconnects | DigiKey

PRFIA-185-J-J-S - Adapter Coaxial Connector 1.85mm Jack, Female Socket To 1.85mm Jack, Female Socket 50 Ohms from

Fiber Connectors

Key performance characteristics for selecting a connector are discussed, including the insertion loss (attenuation), return loss

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://benniedesignstudio.co.za>

Email: sales@benniedesignstudio.co.za

Phone: +27 82 391 4765

Address: The Towers, 1 St Georges Mall, Cape Town, 8001, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

