

P30 Distribution Box Dimension Table



Summary of Content

The P30 distribution box comes in multiple variants, with sizes ranging from compact enclosures of 6.62" x 4.64" x 3.51" to full-featured wall-mounted or pedestal-mounted units for EV charging and power distribution.

KeContact P30 Wallbox (EV Charging) Specifications

- Mounting Options: Wall-mounted or free-standing on a stainless steel pedestal, suitable for indoor and outdoor use .
- Electrical Features: Integrated DC fault current monitoring eliminates the need for upstream FI type B, reducing installation costs .
- Power Output: Entry-level e-series supports up to 7.4 kW; higher series offer more advanced features .
- Communication & Control: Supports OCPP 1.5/1.6, UDP, and Modbus TCP for smart home integration, load management, and energy billing .
- Energy Metering: Integrated MID-certified energy meter allows accurate billing and monitoring of energy usage .
- Connectivity: Can connect up to fifteen c-series wallboxes to an x-series master for local load management .

Moristech P30 Power Distribution Module (PDM) Specifications

- Channels: 30-channel fuse-less system distributing 8 outputs at 20A and 22 outputs at 8A .
- Connectivity: Onboard CAN BUS system compatible with 8, 12, and 15-button Greyhill keypads .

Article Content

KeContact P30 Datenblatt E dd

KeContact P30 can easily be connected to a central system via OCPP 1.5. This is of particular interest for monitoring, load

KeContact P30

KeContact P30 is available in four different equipment series. The series are built upon each other, which means that, when purchas

KeContactP30TechnicalData_dben

This data sheet lists various design options for the charging station. The actual design of the charging station depends on the variant.

KeContact P30

Unsere KeContact P30 ist dabei sowohl für den Innen- als auch für den Außenbereich geeignet. Die Montage erfolgt je nach Bedarf,

KeContactP30TechnicalData_dbde

Bei Belüftungsanforderung vom Fahrzeug wird kei-ne Ladung gestartet. Max. Ausgangsstrom: Max. Datenrate: Max. Datenrate:

KeContact_P30_TechnicalData_dbde

Gilt nur für KeContact P30 Geräte, die ein VDE-Prüfzeichen am Typenschild aufgedruckt haben. Dieses Datenblatt listet

P30,BK Serpac | Boxes | DigiKey

P30,BK - Enclosure Black Cover Included 6.620" L x 4.640" W (168.15mm x 117.86mm) X 3.510" (89.15mm) from Serpac. View

Distribution Boxes Technical Data

8-port ... NPN Wiring diagram shows both PNP and NPN wiring. Actual units use PNP status indicator, NPN status indicator, or

KeContact P30

Our KeCon-tact P30 is suitable for both indoor and outdoor use. Depend-ing on requirements, it can be mounted on the wall or free

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://benniedesignstudio.co.za>

Email: sales@benniedesignstudio.co.za

Phone: +27 82 391 4765

Address: The Towers, 1 St Georges Mall, Cape Town, 8001, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

